

NEW CYLINDRIQUE HAMMER PAJOT 800 C / 1200 C

SPECIFICATIONS

800 C

1200 C

Approx. weight (without guide)	800 kg.....	1 200 kg
Approx. weight (with can)	around 1 265 kg.....	around 1 714 kg
Impact energy at 8 bar	455 kg.m.....	700 kg.m
Blow rate	250 BPM.....	240 CPM
Air required flow rate	9 000 L/minute.....	11 000 L/minute
Hose diameter.....	40 mm.....	40 mm

This hammer can be fitted with :

- ⋮ 1 tube guide up to Ø 440 mm
- ⋮ 1 sheet pile guide (single or double)
- ⋮ Under water job set-up

SPECIFIC BENEFITS OF THE NEW "C" HAMMERS

- ⋮ Less parts breakage risk
- ⋮ Less troubles and maintenance task
- ⋮ Reducing wear parts consumption
- ⋮ Easier breakdown diagnostic
- ⋮ More reliable and robust set-up
- ⋮ Easier guide system adaptable to all type of profil
(tube, H beam, double and single sheet pile, etc...)
- ⋮ Manufacturing time reduced






NEW CYLINDRIQUE HAMMER PAJOT 800 C / 1200 C

FURTHER INFORMATIONS

Maximum practical load able to be exerted on a pile : 15 tons.

Work capacity in a medium ground :

- ⋮ 400 mm single sheet pile, 6 to 8 meters in ground and 5 meters double sheet piles
- ⋮ Pointing closed tubes diam. 250 mm, 16 meters in ground
- ⋮ Open tubes diam. 350 mm, 8 meters in ground



Leg guide for sheet piles, H, tubes, wooden piles